

# SPECTRO LUBRICANT TECHNICAL DATA

## Spectro Hypoid Gear Lubricant



### Description

Spectro Hypoid is a hypoid gear lubricant formulated with the highest density and highest V.I. petroleum base stocks available. Special EP additives are used to reduce pinion gear wear. API GL-5 rated.

Meets all known OEM warranty requirements.

### Application

Spectro Hypoid product is designed for the final drives and transmissions of all shaft drive motorcycles that do not have a wet clutch, including BMW®, MotoGuzzi®, older Harleys®, and Big Twins.

### Typical Inspections

	<b>80W90</b>
Kinematic Viscosity @ 100° C cST	14.4
Kinematic Viscosity @ 40° C cST	134.0
Flash Point, °C	290
Pourpoint, °C	-22
Viscosity Index	105

### Code

L.HYP  
X.HYP

### Description

12/1 Liter Bottles  
1/16 Gal. Keg

### Weight

25 Lbs.  
120 Lbs.

- EXCEPTIONALLY HIGH EP ANTI-WAR ADDITIVE TREATMENT REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT CONDITIONS.
- HIGHEST LUBRICITY AND SHEAR STABILITY.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API GL-5

**SPECTRO OILS OF AMERICA**  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)

